



MODEL NUMBER:
 CF-521011-LED-10-A-06 CF-521011-LED-10
 (BRUSHED NICKEL)
 CF-521011-LED-20 (OIL RUBBED BRONZE)
 CF-521011-LED-30 (WHITE)
 CF-521011-LED-40 (BLACK)

52 in. Tramontana Ceiling Fan

With “Quick Connect” blade installation feature.



- 52 in. Sweep 5 Blades
- 153 mm X 13 mm Silicon Steel Motor
- 12 degree Blade Pitch
- Triple Capacitor, Dry Location
- Frosted White Glass Dome
- 3 LED 9 Watt Soft-White Bulbs
- Compliant with DOE and CEC Energy Efficiency Regulations
- Limited Lifetime Warranty (Fan Motor Only)
- Classic Look Ceiling Mount

SPECIFICATIONS

ITEM NUMBER	CF-521011-LED-XX
FINISH	Brushed Nickel, Oil Rubbed Bronze, White, Black
CATEGORY	Ceiling Fan
INDOOR/OUTDOOR	Indoor
BLADE MATERIAL	MDF
BLADE FINISH OPTIONS	Chrome, Rosewood, Black Gloss/Rosewood, Silver Oak/Rosewood, Black Forest/Rosewood
DIMENSIONS	52 in. x 18.88 in.
NUMBER OF BLADES	5
MOTOR SPECS	153 mm x 13 mm AC
CONTROLS	Pull Chain Switch
DOWN ROD	4.5 in.
LEAD WIRE	80 in.
BLADE PITCH	12 deg.
BLADES LOWEST POINT TO CEILING	13 in.
LIGHT KIT	E26 x 3
SHADE MATERIAL	Glass
SHADE DESCRIPTION	Frosted Opal Glass
NUMBER OF SHADES	1
SHADE DIMENSIONS	12 in. Dia. x 3.9 in Depth

PERFORMANCE

WATTAGE	9.5 W x 3		
COLOR TEMP	3000K		
CRI	≥90		
INITIAL LUMENS	800lm		
DELIVERED LUMENS			
BULB/LED INCLUDED	Yes		
DIMMABLE	No		
OPERATING VOLTAGE	120V, 60Hz		
HARDWARE FINISH OPTIONS	ORB, White, Black, ST		
LABELS	ETL Dry Location Listed		
	LOW	MEDIUM	HIGH
RPM	64-68	115-128	174-180
AMPS	0.22	0.35	0.51
WATTS	10.54	28.5	60.8
AVERAGE AIRFLOW (CFM AVE.)	3280		
AIRFLOW EFFICIENCY (CFM/W)	88		