

Vinyl Plank Flooring



This collection is self-expressive and inspired by worldly travels. This collection is carefree and unexpected. Highlight this collection by layers of color and pattern to create an upbeat energy.

VARIATIONS

PROPERTIES	PRIMAFLOOR	ENVIROFLOOR	
Composition	100% Virgin Vinyl	30% Recycled Material	
Thickness	2-mm & 3-mm	2-mm	
Dimensions	6-in x 36-in & 7-in x 48-in	6-in x 36-in & 7-in x 48-in	
Wear Layer*	6-mil, 8-mil, & 12-mil	6-mil, 8-mil, & 12-mi	

^{*} Wear layer has a UV-polyurethane coating to reduce maintenance.

CERTIFICATION

DESCRIPTION	STANDARD	RESULT
Solid Vinyl Tile	ASTM F1700	Class III, Type B
Fire Response	ASTM E648 & E662	Pass (Class I)
Residual Indentation	EN 433:1994	Pass
Light Resistance	ASTM F1515	Pass
Heat Resistance	ASTM F1514	Pass
Chemical Resistance	ASTM F925	Pass
Flexibility	ASTM F137	Pass
Dimensional Stability	ASTM F2199	Pass
Overall Thickness	ASTM F386	Pass
Abrasion Resistance	ASTM F510	Pass
Sound Insulation**	ISO 7171-2	Pass
Health and Safety	FloorScore, CE, ISO 16000	Pass

^{**} Sound properties will vary depending on the specific flooring and ceiling assembly.

INSTALLATION

Use only Wagonway 1503 or Wagonway 1520 adhesives, or equivalent.

WARRANTY

Wagonway provides a 7-year warranty for light commercial applications. Please visit www.wagonway.com for full warranty details.

LEAD TIME

The lead time is 45 days from order placement.

For more information, visit us at www.wagonway.com





1074 Eclectic Ash



1031 Unconventional Oak



1003 Free Spirit Ash

BETTER

10 YEAR

7 YEAR LIGHT COMMERCIAL



1068 Vintage Hickory