



# Vinyl Plank Flooring



## INDUSTRIAL



The collection evokes a warehouse vibe with weathered elements. This collection personifies a rugged masculine style that can be complemented with the use of exposed metals, brick, and darker colors.

### VARIATIONS

PROPERTIES	PRIMAFLOOR	ENVIROFLOOR
Composition	100% Virgin Vinyl	30% Recycled Material
Thickness	2-mm & 3-mm	2-mm
Dimensions	6-in x 36-in & 7-in x 48-in	6-in x 36-in & 7-in x 48-in
Wear Layer*	6-mil, 8-mil, & 12-mil	6-mil, 8-mil, & 12-mi

\* Wear layer has a UV-polyurethane coating to reduce maintenance.

### CERTIFICATION

DESCRIPTION	STANDARD	RESULT
Solid Vinyl Tile	ASTM F1700	Class III, Type B
Fire Response	ASTM E648 & E662	Pass (Class I)
Residual Indentation	EN 433:1994	Pass
Light Resistance	ASTM F1515	Pass
Heat Resistance	ASTM F1514	Pass
Chemical Resistance	ASTM F925	Pass
Flexibility	ASTM F137	Pass
Dimensional Stability	ASTM F2199	Pass
Overall Thickness	ASTM F386	Pass
Abrasion Resistance	ASTM F510	Pass
Sound Insulation**	ISO 7171-2	Pass
Health and Safety	FloorScore, CE, ISO 16000	Pass

\*\* Sound properties will vary depending on the specific flooring and ceiling assembly.

### INSTALLATION

Use only Wagonway 1503 or Wagonway 1520 adhesives, or equivalent.

### WARRANTY


Wagonway provides a 7-year warranty for light commercial applications. Please visit [www.wagonway.com](http://www.wagonway.com) for full warranty details.

### LEAD TIME


The lead time is 45 days from order placement.

For more information, visit us at [www.wagonway.com](http://www.wagonway.com)

### AVAILABLE COLORS




1062 Black Steel Oak



1048 Galvanized Grey Ash



1047 Weathered Oak



1044 Copper Ash



1051 Rugged Bronze

